



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
-----------------	-------------	----------------------	---------------------	------------------

10/754,403

01/09/2004

Takumi Yamaguchi

10873.1377US01

7971

53148

7590

12/13/2007

HAMRE, SCHUMANN, MUELLER & LARSON P.C.

P.O. BOX 2902-0902

MINNEAPOLIS, MN 55402

EXAMINER

PETERSON, CHRISTOPHER K

ART UNIT

PAPER NUMBER

2622

MAIL DATE

DELIVERY MODE

12/13/2007

PAPER

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

<b>Office Action Summary</b>	Application No. 10/754,403	Applicant(s) YAMAGUCHI ET AL.	
	Examiner Christopher K. Peterson	Art Unit 2622	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

#### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

#### Status

- 1) ☒ Responsive to communication(s) filed on 05 July 2007.
- 2a) ☒ This action is **FINAL**.                      2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

#### Disposition of Claims

- 4) ☒ Claim(s) 1-20 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-20 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

#### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
     Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
     Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

#### Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All    b) ☐ Some \*    c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- \* See the attached detailed Office action for a list of the certified copies not received.

#### Attachment(s)

- |  |   |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892)                                | 4) <input type="checkbox"/> Interview Summary (PTO-413)<br>Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)                       | 5) <input type="checkbox"/> Notice of Informal Patent Application                       |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)<br>Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____  |

## **DETAILED ACTION**

### ***Response to Amendment***

1. The Amendment After Non-Final Rejection filed on July 5, 2007 has been received and made of record. Examiner notes that the Applicant has amended claims 1 and 2 and added claims 19 – 20.

### ***Response to Arguments***

2. Applicant's arguments with respect to claims 1 - 18 have been considered but are moot in view of the new ground(s) of rejection.

### ***Claim Rejections - 35 USC § 103***

3. The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.
4. Claims 1 – 5 and 8 - 20 are rejected under 35 U.S.C. 103(a) as being unpatentable over Voss (US Patent # 7,233,354) in view of Fossum (US Patent # 5,949,483).

As to claim 1, Voss teaches a solid-state imaging device, comprising:

- an imaging region (CMOS sensor 24) in which a plurality of pixels are arranged (Col. 4, lines 41 – 44); and
- wherein an adding circuit (CMOS sensor 24, variable analog amplifier 26, A/D converter 28, microprocessor 32 and memory card 38) for adding pixel signals obtained from two or more of the pixels is provided so that an output

signal of the adding circuit is read out to the signal line (Col. 6, line 53 – 59), the adding circuit comprising an adding portion (summed pixels Col.6, lines 57 - 59), a gain control portion (variable analog amplifier 26) and a storage portion (memory card 38), so that an output of the adding circuit (24) is subjected to a gain control by the gain control portion (26) and then stored in the storage portion(38) (Col. 4, lines 61 – 65), and

- wherein on the basis of a predetermined reference quantity of light (light-level sensor 55) incident onto the imaging region (24), a gain of the adding circuit in a condition in which a quantity of the incident light is above the reference quantity is controlled to be smaller than a gain of the adding circuit in a condition in which a quantity of the incident light is below the reference quantity (Col. 5 line 54 – Col.6, line 4). Voss teaches the microprocessor decides to adjust the gain, resolution, or both depending on the light-level sensor (55). The microprocessor would provide a small gain when in the incident light is high and provide a large gain for low incident light (Col. 5 line 62 – Col.6, line 4).

Voss does not teach a signal line through which a pixel signal of the imaging region is read out. Fossum (Fig. 8) teaches a signal line (output signals from multiplexer 612) through which a pixel signal of the imaging region is read out (Col. 11, lines 34 – 40).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to have provided signal line through which a pixel signal of

the imaging region is read out as taught by Fossum to the imaging device of Voss, because a multi-resolution readout system that can provide image data at a desired resolution and at speeds greater than or equal to the aforementioned video rates Col. 2, lines 47 – 50 of Fossum)

As to claim 2, Voss teaches a solid-state imaging device, comprising:

- an imaging region (CMOS sensor 24) in which a plurality of pixels are arranged (Col. 4, lines 41 – 44); and
- wherein an adding circuit (CMOS sensor 24, variable analog amplifier 26, A/D converter 28, microprocessor 32 and memory card 38) for adding pixel signals obtained from two or more of the pixels is provided so that an output signal of the adding circuit is read out to the signal line (Col. 6, line 53 – 59), the adding circuit comprising an adding portion (summed pixels Col.6, lines 57 - 59), a gain control portion (variable analog amplifier 26) and a storage portion (memory card 38), so that an output of the adding circuit (24) is subjected to a gain control by the gain control portion (26) and then stored in the storage portion(38) (Col. 4, lines 61 – 65), and
- wherein within at least a partial range of a quantity of incident light onto the imaging region (24), a gain of the adding circuit is controlled to decrease with an increase of the quantity of the incident light (Col. 5 line 54 – Col.6, line 4). Voss teaches the microprocessor decides to adjust the gain, resolution, or both depending on the light-level sensor (55). The

microprocessor would provide a small gain when in the incident light is high and provide a large gain for low incident light (Col. 5 line 62 – Col.6, line 4).

Voss does not teach a signal line through which a pixel signal of the imaging region is read out. Fossum (Fig. 8) teaches a signal line (output signals from multiplexer 612) through which a pixel signal of the imaging region is read out (Col. 11, lines 34 – 40).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to have provided signal line through which a pixel signal of the imaging region is read out as taught by Fossum to the imaging device of Voss, because a multi-resolution readout system that can provide image data at a desired resolution and at speeds greater than or equal to the aforementioned video rates Col. 2, lines 47 – 50 of Fossum)

As to claim 3, Voss in view of Fossum teaches wherein the adding circuit (24, 26, 28, 32 and 38 of Voss) is arranged between the imaging region (image array 602 of Fossum) and the signal line (output signals from multiplexer 612 of Fossum).

As to claim 4, Voss teaches the solid-state imaging device according to claim 1, wherein a plurality of the adding circuits are arranged between the two or more pixels included in the respective sets of pixels (Col. 6, lines 50 – 53).

As to claim 5, Voss teaches the solid-state imaging device according to claim 1, wherein a plurality of the adding circuits are provided, and gains for at least two of the plurality of adding circuits are controlled individually (Col.6., line 50 – 67). Voss teaches

the summing function occurs before any gain is applied to the signal (Col. 6, line 59 – 64). This increases the signal to noise ratio.

As to claim 8, note the discussion above. Voss does not teach an adding circuit is provided with an averaging portion. Fossum (Fig. 7 and 8) teaches an averaging portion (608 and 610) for averaging pixel signals obtained from two or more of the pixels (Col. 11, lines 3 – 40). Fossum (Fig. 8) shows how a block of 3 x 3 would be processed through the averaging circuit (608 and 610) (Col. 11, lines 23 – 32). Fossum also teaches the multi-resolution readout architecture can be set by programmable switches (Col. 12, lines 14 - 20). The microprocessor of Voss and the programmable switches of Fossum could be the same unit. When the quantity of incident light is larger than a predetermined higher reference quantity that is larger than the reference quantity, an output of the averaging portion is read out to the signal line in place of the added signal (Col. 11, lines 3 – 40). Fossum (Fig. 8) shows how a block of 3 x 3 would be processed through the averaging circuit (608 and 610) (Col. 11, lines 23 – 32).

As to claim 9, Voss teaches wherein when signals of N pieces of pixels (added pixels) are added, a gain of the adding circuit (24, 26, 28, 32 and 38) is controlled so that an output value from the adding circuit is not more than a value obtained from the following formula:  $(\text{value obtained by adding the N pieces of signals}) / N$  (Col. 5 line 62 – Col. 6, line 4). Voss teaches the microprocessor decides to adjust the gain, resolution, or both depending on the light-level sensor (55). The microprocessor would provide a small gain when the incident light is high and provide a large gain for low incident light (Col. 5 line 62 – Col. 6, line 4).

As to claim 10, Voss teaches wherein when signals of N pieces of pixels are added, a gain of the adding circuit (24, 26, 28, 32 and 38) is controlled so that an output value from the adding circuit is less than a value obtained by adding the N pieces of signals and more than a value obtained from the following formula: (value obtained by adding the N pieces of signals) / N (Col. 5 line 62 – Col.6, line 4). Voss teaches the microprocessor decides to adjust the gain, resolution, or both depending on the light-level sensor (55). The microprocessor would provide a small gain when in the incident light is high and provide a large gain for low incident light (Col. 5 line 62 – Col.6, line 4).

As to claim 11, Voss teaches a camera (10) equipped with the solid-state imaging device according to claim 1 (Col. 3, lines 42 – 51).

As to claim 19, Voss teaches wherein a gain (26) is controlled for each of the plurality of signals (Col. 5, line 54 – Col. 6, line 4). Voss teaches the microprocessor (32) decides if the gain is used or change in resolution.

As to claims 12 – 18 and 20, these claims differ from claims 1, 3, 4, 5 – 11 and 19 only in that the claims 12 – 18 and 20 depend on claim 2 and claims 1, 3, 4, 5 – 11 and 19 depend on claim 1. Thus claims 12 – 18 and 20 are analyzed as previously discussed with respect to claims 1, 3, 4, 5 – 11 and 19 above.

5. Claims 6 and 7 are rejected under 35 U.S.C. 103(a) as being unpatentable over Voss (US Patent # 7,233,354) in view of Fossum (US Patent # 5,949,483) as applied to claims 3 and 4 above, and further in view of Takayama (US Patent # 7,088,395).



As to claim 6, note the discussion of Voss in view of Fossum above, Voss in view of Fossum do not teach a photometer portion is provided between the imaging region and the signal line so as to detect a quantity of the incident light onto the imaging region. Takayama teaches a photometer portion (150b) is provided between the imaging region (54) and the signal line (w1 and w2) so as to detect a quantity of the incident light onto the imaging region (54).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to have provided a photometer portion is provided between the imaging region and the signal line so as to detect a quantity of the incident light onto the imaging region as taught by Takayama to the image capturing device of Voss in view of Fossum, because the image-capturing apparatus will reduce its power consumption, low-cost and reduce the number of necessary parts (Col. 2, line 62 – Col. 3, line 10 of Takayama).

As to claim 7, claim 7 cites a photometer portion is arranged between the two or more pixels as to claim 6. Takayama teaches a photometer portion (50b in Fig. 4) is arranged between the two or more pixels (50a).

### ***Conclusion***

6. **THIS ACTION IS MADE FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire **THREE MONTHS** from the mailing date of this action. In the event a first reply is filed within

TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Christopher K. Peterson whose telephone number is 571-270-1704. The examiner can normally be reached on Monday - Friday 6:30 - 4:00 EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, NgocYen Vu can be reached on 571-272-7320. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

CKP/JM  
12/6/07

  
NGOCYEN YU  
SUPERVISORY PATENT EXAMINER